

Mini Balance Microphone Cable 迷你平衡式麥克風線

- The characteristics of small and low capacitance.
- Filled with NYLON FIBER, very suitable for small microphones and hanging microphones.
- 具有細小及低電容的特性。
- 尼龍絲填充，非常適合小型麥克風及吊掛麥克風使用。



Item no. 型號	Jacket Color 外被顏色	Conductor 導體	Jacket OD 外徑
3070100082	4 Colors	(10/0.10+250D NYLON FIBER+PE0.85)*1P	3.0mm

Item No. 型號 3070100082

Wire Information 線材資料	(10/0.10+250D NYLON FIBER+PE0.85)*1P +COTTON YARN+BD16*5/0.10+PVC3.0
Main Conductor(AWG) 主要導體截面積	29AWG
Main Conductor(mm ²) 主要導體截面積	0.079mm ²

Electrical Performance 電氣性能

Cond.D.C.R. ohm/1km 導體電阻	<227+/-5%Ω
Shield.D.C.R. ohm/1km 屏蔽電阻	<27Ω
Capacitance(pF/m) 電容值	C1 <59 C0 <109
Inductance(μH/m) 電感值	L1 --- L0 ---
Impedance(ohm) 特性阻抗	---
Voltage Breakdown 絕緣承受電壓	300V

Mechanical Performance 機械性能

Flex Life Number of Times load 500g+/-30° 搖晃壽命次數負載 500g 角度+/-30°	>31600
Tensile Strength (26°C, 65%RH) 拉伸斷裂力量	>23.9kgf
Applicable Temperature 建議工作溫度	-20°~+60°C(-4°~+140°F)
Peak Temperature 極限工作溫度	-20°~+70°C(-4°~+158°F)
100m Weight(kg) 100m 重量	1.4+/-0.2

- The tensile strength is up to 23.9kgf.
- 拉伸斷裂力量高達23.9kgf。

■ Black 黑 3070100082
 ■ Orange 橘 3070100083
 □ White 白 3070100084
 ■ Gold 金 3070100148



Item no. 型號	Jacket Color 外被顏色	Conductor 導體	Jacket OD 外徑
3070100001	3 Colors	(10/0.10+250D NYLON FIBER+PE1.0)*1P	3.3mm

Item No. 型號 3070100001

Wire Information 線材資料	(10/0.10+250D NYLON FIBER+PE1.0)*1P +COTTON YARN+SP40/0.10+PVC3.3
Main Conductor(AWG) 主要導體截面積	29AWG
Main Conductor(mm ²) 主要導體截面積	0.079mm ²

Electrical Performance 電氣性能

Cond.D.C.R. ohm/1km 導體電阻	<256+/-5%Ω
Shield.D.C.R. ohm/1km 屏蔽電阻	<61Ω
Capacitance(pF/m) 電容值	C1 <51 C0 116
Inductance(μH/m) 電感值	L1 --- L0 ---
Impedance(ohm) 特性阻抗	---
Voltage Breakdown 絕緣承受電壓	300V

Mechanical Performance 機械性能

Flex Life Number of Times load 500g+/-30° 搖晃壽命次數負載 500g 角度+/-30°	>27000
Tensile Strength (26°C, 65%RH) 拉伸斷裂力量	>30kgf
Applicable Temperature 建議工作溫度	-20°~+60°C(-4°~+140°F)
Peak Temperature 極限工作溫度	-20°~+70°C(-4°~+158°F)
100m Weight(kg) 100m 重量	1.4+/-0.2

- The tensile strength is up to 30kgf.
- 拉伸斷裂力量高達30kgf。

■ Black 黑 3070100001
 ■ Orange 橘 3070100003
 □ White 白 3070100002

※ Electrical performance may have manufacturing tolerances and measurement errors. At the time of editing, every effort has been made to ensure its authenticity.
 電氣性能可能存在製造公差與量測誤差；本資料在編輯時已盡力保證其真實性。