



REVISIONS		
ISS	ZONE	DESCRIPTION\PER REQUEST\DATE
A5	B-7	增加ST359L-B-C01品名,增加備註2
V	OPEN	對客戶公開圖紙
	OPEN	對供應商公開圖紙
	CLOSED	僅限廠內使用

- Notes(備註):
- The plastic seat is separated from the copper screw, and the jacking force is >5kg.
(塑座與銅螺桿分離頂出力>5kg.)
 - The plastic nut is separated from the knurled nut, and the jacking force is > 4kg.
(塑膠螺母與滾花螺母的分離頂出力>4kg.)
 - The contact resistance of the banana head should be less than 3 milliohms, and the banana head should be inserted smoothly.
(配插上香蕉頭接觸電阻<3毫歐,配插香蕉頭要順暢)
 - The color of the color circle refers to Pantone card: Red/185C, Green/354C.
(色圈顏色參考Pantone(彩通)色卡:紅色/185C, 綠色/354C)
 - Parts 5,6 and 8 don't need to be assembled, and are packaged separately.
(零件5,6,8不用組裝,單獨分類包裝)

台灣日昇電子股份有限公司
ISSUE APPROVED
 發行核可 本文件與簽核紙本正本相符

List:

ERP link(品號)	半成品品號(外)		Part No.(品名)	Plastic base / Nut color (塑座及塑膠螺母顏色)	Color ring color (色圈顏色)
5116020002	5116020021	1601160071	ST359L-C01-RD	Gray(灰色)	Red(紅色)
5116020001	5116020020	1601160070	ST359L-C01-BK		Black(黑色)
5116020003	5116020022	1601160072	ST359L-C01-GN		Green(綠色)
5116020015			ST359L-B-C01-BK	Black(黑色)	Black(黑色)
5116020016			ST359L-B-C01-RD		Red(紅色)

NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.
8	六角螺母(HEX. NUT) (M8x1.25)	A3	鍍鎳(NICKEL)	1	
7	螺桿(SCREW POST)	H59-1	鍍鎳(NICKEL)	1	
6	六角螺母(HEX. NUT) (M5x0.8)	A3	鍍五彩鋅(ZINC COLORFUL)	1	
5	墊圈(WASHER)	A3	鍍鎳(NICKEL)	1	
4	塑座(PLASTIC BASE)	PA	List	1	
3	滾花螺母(KNURL NUT)	H59-1	鍍鎳(NICKEL)	1	
2	塑膠螺母 (PLASTIC NUT)	PA	List	1	
1	色圈(COLOR RING)	PA	List	1	

DIMENSIONS ARE IN MILLIMETERS
 UNLESS OTHERWISE SPECIFIED
 TOLERANCES
 ANGLES = ±5'
 UP TO 6 = ±0.2
 6-40 = ±0.4
 40-120 = ±0.6
 120-315 = ±1
 ABOVE 315 = ±1.6

THIRD_ANGLE $\frac{1}{2}$
 SCALE 3/1

APPROVED *蘇其* DATE 2023-11-15
 CHECKED DATE
 DRAWN 吳碧珊 DATE 2023-11-15
 FILE NO. D:\CAD\IST系列\5116020001_
 ST359L-C01-BK_CA001A5
 ERP LINK: 5116020001

SUNRISE 日昇電子股份有限公司
 SUN RISE EXACT INDUSTRIAL CO.
 TITLE
 BINDING POST WITH COLOR RING:
 BLACK & GREEN & RED
 PART NO. ST359L-C01-BK
 REV. A5