

REVISIONS		
ISS	ZONE	DESCRIPTION\PER REQUEST\DATE
A4	ALL	43.2改公差為±1,零件表新增塑料套,刪除15.8和6.4
	OPEN	對客戶公開圖紙
	OPEN	對供應商公開圖紙
	CLOSED	僅限廠內使用

Technique requests(技術要求):


- Sleek in appearance, burr in periphery (外表光滑,無毛邊)
- Thread can screw in smoothly (螺牙旋入順暢)
- It should match the male connector smoothly. (母座配插順暢)

Electrical(電氣性能):	
Contact resistance(接觸電阻)	10mΩ max.
Insulator resistance(絕緣電阻)	1000MΩ min.
Current rating(耐電流)	8P/4A
Withstand voltage(耐電壓)	1500 VAC

台灣日昇電子股份有限公司
ISSUE APPROVED
發行核可
本文件與簽核紙本正本相符

NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.
8	壓線蓋螺絲(WIRE-CLAMP SCREW)	A3	鍍鎳(NICKEL)	2	1601140093
7	壓線蓋(WIRE-CLAMP COVER)	ZZnAL4-0	鍍鎳(NICKEL)	1	
6	塑料套(PLASTIC TUBE)	P.P.		1	
5	外殼(SHELL)	ZZnAL4-0	鍍鎳(NICKEL)	1	
4	塑粒(INSULATOR)	膠木(BAKELITE)	黑色(BLACK)	1	
3	螺絲(SCREW)	A3	鍍鎳(NICKEL)	1	
2	插針(PIN)	H59-1	鍍銀(SILVER)	8	
1	本體(BODY)	ZZnAL4-0	鍍鎳(NICKEL)	1	

DIMENSIONS ARE IN MILLIMETERS		APPROVED	DATE
UNLESS OTHERWISE SPECIFIED TOLERANCES		2023-11-03	
ANGLES = ±5°		CHECKED	DATE
UP TO 6 = ±0.2		2023-11-01	
6-40 = ±0.4		DRAWN	DATE
40-120 = ±0.6		吳碧珊	2023-11-01
120-315 = ±1		FILE NO.	D:\CAD\SVP564\5114030009_
ABOVE 315 = ±1.6		SVP564C-8P_CA001A4	
THIRD_ANGLE	☉	ERP LINK:	5114030009
SCALE	2/1	PART NO.	SVP564C-8P

 日昇電子股份有限公司 SUN RISE EXACT INDUSTRIAL CO.		TITLE	
		8P CIRCULAR MALE PLUG, M16mm	
REV.		A4	