

Hole: 19\*24mm, Size: 26\*31mm

## D Type XLR Socket

### IP54 Waterproof Solder Cup

Plastic Shell, Silver Plated Pin

Male, 3/5P **SVP555P-WP**




Female, 3P **SVP561P-S-3.5-WP**




### IP65 Waterproof Solder Cup

Plastic Shell, Silver Plated Pin, 3P

Female, 4 Holes **SVP561WP**



Female, 2 Holes **SVP561WP-D2**



Item No. -PG, PG: Gold Plated Pin

#### IP54 Rating:

- (5) Solids: Dust Protected. Limited ingress of dust permitted. Will not interfere with operation of the equipment. Two to eight hours.
- (4) Water: Protected against water splashed from all directions. Limited ingress permitted.

#### IP65 Rating:

- (6) Solids: Dust tight. No ingress of dust. Two to eight hours.
- (5) Water: Protected against jet of water. Limited ingress permitted.

- ※ SVP555P-WP must be matched with SVP556X-WP to achieve IP54.
- ※ SVP561P-S-3.5-WP must be matched with SVP555X-WP to achieve IP54.
- ※ SVP561WP and SVP561WP-D2 must be matched with SVP555X-WP to achieve IP65.



SVP555X-WP




SVP556X-WP

### Solder Cup

Plastic Shell, Silver Plated Pin, 3P

Male  
**SVP555P-S-3.5**



Female  
**SVP561P-S-3.5**



Nickel Finish Shell, Silver Plated Pin, 3/4/5P

Male  
**SVP555AX**



Female  
**SVP561NX**



Male  
**SVP555A-N**



Female  
**SVP561N**



Electrophoresis Black Shell, Gold Plated Pin, 3/4/5P

Male  
**SVP555AX-BK-PG**



Female  
**SVP561NX-BK-PG**



Male  
**SVP555A-N-BK-PG**

Female  
**SVP561N-BK-PG**



### PCB Pin

Female, UL 94V-0 Standard

**SVP561P-D-AP-94V0**


Plastic Shell, Silver Plated Pin, 3P



Male, Right Angle PCB Pin

**SVP555A-N-R**

Can be Rear-mounted, Only 3P



### D Type PVC Protective Cover

Hole: 19\*24mm

**1CE0033**



**1CE0040**



**1CE0041**



**1CE0042**



**1CE0043**



D Type Standard Size  
19\*24  
26\*31

Available Cover for D Type Socket	Item No.	Male XLR	Female XLR	Cat5E RJ45 Socket	Speaker/Power Socket
	<b>1CE0033</b>	•	•	•	•
	<b>1CE0040</b>		•	•	
	<b>1CE0041</b>	•			•
	<b>1CE0042</b>	•			•
	<b>1CE0043</b>		•		•