

## PVC Twisted Pair Speaker Cable PVC對絞型喇叭線

Black/Red Twisted Pair Speaker Cable



Blue/Transparent Twisted Pair Speaker Cable



Main Conductor 主要導體截面積		Black/Red Item No. 黑/紅色型號	Blue/Transparent Item No. 藍/透明色型號	Conductor 導體	Jacket OD(mm) 外徑	Cond.D.C.R. ohm/1km 導體電阻	Capacitance(pF/m) between Conductors 導體間電容值	Voltage Breakdown 絕緣承受電壓
AWG	mm <sup>2</sup>							
	4.0	307070197N	3070700197	80/0.254	10.0	4.31	196.02	300V or better
12	3.294	307070188N	3070700188	65/0.254	9.0	5.43	195.82	
	2.5	307070172N	3070700172	50/0.254	8.2	7.5	176.8	
14	2.077	307070189N	3070700213	41/0.254	8.0	8.62	161.84	
	1.5	307070173N	3070700173	30/0.254	7.2	12.5	142.06	
16	1.307	307070198N	3070700198	65/0.16	7.0	13.7	130.62	
18	0.824	307070199N	3070700199	41/0.16	6.0	21.8	113.67	
20	0.522	307070200N	3070700200	26/0.16	5.5	34.6	80.49	

### Wire Information 線材資料

Black/Red Twisted Pair Speaker Cable 黑/紅色對絞型喇叭線	(OFC+Black PVC/OFC+Red PVC)+Gray PVC (無氧銅+黑 PVC/無氧銅+紅 PVC)+灰 PVC
Blue/Transparent Twisted Pair Speaker Cable 藍/透明色對絞型喇叭線	(OFC+Blue PVC/TC+ Transparent PVC)+ Transparent PVC (無氧銅+藍 PVC/鍍錫銅+透明 PVC)+透明 PVC

### Mechanical Performance 機械性能

Flex Life Number of Times load 500g+/-30° 搖晃壽命次數負載 500g 角度+/-30°	---
Tensile Strength (26°C, 65%RH) 拉伸斷裂力量	---
Applicable Temperature 建議工作溫度	-20°C~ +60°C(-4°F~ +140°F)
Peak Temperature 極限工作溫度	-20°C~ +70°C(-4°F~ +158°F)

※ Electrical performance may have manufacturing tolerances and measurement errors. At the time of editing, every effort has been made to ensure its authenticity.  
電氣性能可能存在製造公差與量測誤差；本資料在編輯時已盡力保證其真實性。