

XLR Connector

Victor Series \varnothing 3.3~7mm, 3P

- Drip and dust proof boot.
- Zinc shell thread structure, makes the lock screws tightly.
- Inner lock for longer service life of male XLR.

Male
SVP555V
Female
SVP556V

Nickel Finish Shell
Gray Boot
Silver Plated Pin



Adapt Multiple Wire Diameters

Standard White Clamp: 5.0~6.8mm
Take Off Washer: 3.3~4.8mm
Black Clamp: 7.0~8.0mm (By Order)

Male
SVP555V-BK-PG
Female
SVP556V-BK-PG

Electrophoresis Black Shell
Gray Boot
Gold Plated Pin



IP65 Waterproof Shark Series \varnothing 5.5~6mm, 3/5P

- **Waterproof Clamp:** The round shape does not damage the wires.
- **Female XLR Enclosed Latch:** Completely impermeable.
- **Female XLR Body:** Spring-free, smooth and easy to assemble. Follow AES48-2005 standard, cancels the shell grounding.
- **Female XLR T-washer:** Default color is orange, black is also optional.
- **O-ring:** The orange boot is orange color, and the others are black.
- **Boot:** Soft TPR+ NYLON double-mold injection, strengthen structure. In addition, there is 8mm special boot for option.

Male
SVP555X-WP
Female
SVP556X-WP

Nickel Finish Shell
Orange Boot
Silver Plated Pin



T-washer O-ring Boot



Male
SVP555X-WP-BK-PG
Female
SVP556X-WP-BK-PG

Electrophoresis Black Shell
Gray Boot
Gold Plated Pin



※ This series connector with China PAT. No.: ZL 201310391020.1 ZL 201320540187.5 ZL 201520412969.9

IOT Network + Power

IP65 Waterproof Shark E10 Series \varnothing 8.5mm \downarrow , 10P

- In response to big current power and Ethernet systems.
- Connect through single connector and hybrid cable .
- Suitable for lighting, Internet of Things and industrial control.
- Signal cable recommended: Cat5E.

	Power	Data
Number of Pins	2	8
Current Rating Per Contact	16A	32A
Wire Size	14AWG/2.5mm ²	14AWG/1mm ²
Insertion Force	≤20N	
Withdrawal Force	≤ 20N	
Contact Resistance	≤3mΩ	
Dielectric Strength	1kVd	

Male
SVP555X-WP-E10-PG
Female
SVP556X-WP-E10-PG

Nickel Finish Shell
Blue Boot
Blue O-Ring
Gold Plated Pin



Item No. Rule:

① ② - ③ ④ - ⑤ - ⑥

Example:

SVP556 X-WP - BK B - PG - 8mm



	Remark	Define
①	SVP555	XLR Male
	SVP556	Connector Female
②	V	Victor Series
	X-WP	Shark Series
③	X-WP-E10	Shark E10 Series
		Plastic Boot Color
④	B	Black T-washer (Only for Shark Series Female XLR.)
⑤	PG	Gold Plated Pin
⑥	8mm	Victor 8mm Clamp
		Shark 8mm Boot

③ Plastic Boot Color Remark		
	Nickel Shell	Black Shell
Red	RD	BR
Orange	OR	Shark Default BO
Yellow	YL	BY
Green	GN	BG
Blue	BL	Shark E10 Default BU
Purple	PL	BP
White	WH	BW
Gray	GY	Victor Default BK
Black	BN	BB

IP65 Rating

- (6) Solids: Dust tight. No ingress of dust. Two to eight hours.
- (5) Water: Protected against jest of water. Limited ingress permitted.

