

## 1/4" 6.35mm TRS & TS Phone Plug

### CPX Series

Ø 4~7mm



Two step clamp device can be adapted multiple wire diameters. 15.88mm jack pitch.



TRS SP101-CPX  
TS SP102-CPX

TRS SP101-CPX-OR  
TS SP102-CPX-OR



TRS SP101-CPX-GY  
TS SP102-CPX-GY

TRS SP101-CPX-BK-PG  
TS SP102-CPX-BK-PG



TRS SP101-CPX-BO-PG  
TS SP102-CPX-BO-PG

TRS SP101-CPX-BE-PG  
TS SP102-CPX-BE-PG

### X Series

Ø 6.5mm



Two step clamp device can be adapted multiple wire diameters. 15.88mm jack pitch.



TRS SP101X  
TS SP102X

TRS SP101X-GY  
TS SP102X-GY



TRS SP101X-POG  
TS SP102X-POG

TRS SP101X-POG-GY  
TS SP102X-POG-GY

CPX Series Item No. Rule:

SP101/2-CPX - (Gold Plated) - (White Shell & Boot Color)

SP101/2-CPX - (Black Shell & Boot Color) - (Gold Plated)

X Series Item No. Rule:

SP101/2X - (Insert Color) - (Gold Plated) - (Nickel Shell & Boot Color)

SP101/2X - (Insert Color) - (Black Shell & Boot Color) - (Gold Plated)

※ Insert color default is black, and the remark for orange is POG.



Gold Plated Remark				
Remark	Tip	R/S	Solder Pin	Shell
(Default)	Nickel	Nickel	Tin	Nickel/Black
TG	Gold	Nickel	Tin	Nickel/Black
PG	Gold	Gold	Tin	Nickel/Black
G	Gold	Gold	Tin	Gold
GG	Gold	Gold	Gold	Gold

Boot Color Remark												
	Black	Brown	Red	Orange	Yellow	Green	Blue	Purple	Gray	White		
CPX White Shell	(Default)	BN	RD	OR	YL	GN	BL	PL	GY	WH		
CPX Black Shell	BK	BB	BR	BO	BY	BG	BU	BP	BE	BW		
X Nickel Shell	BN	---	RD	(Default)	YL	GN	BL	PL	GY	WH		
X Black Shell	BB	---	BR	BO	BY	BG	BU	BP	BK	BW		