

Hi-End Microphone Cable for Studio

SVC675 Series







Male XLR to Female XLR XLR Black Shells and Gold Plated Pins 3070100081 Twisted Pair Cable

XLR Type: SVP555S-BK-PG, SVP556S-BK-PG

SVC675V-BK-PG-081-□M

Male XLR to Female XLR XLR Black Shells and Gold Plated Pins 3070100081 Cable

※ XLR Type: SVP555V-BK-PG, SVP556SV-BK-PG

Twisted Pair



3070100081 50.45 pF/1m 0.226mm2 8.0mm PE Gray

- Aluminum Foil and dual Braid three-layer shield.
- Very low capacitance with silver-plated cooper conductor.

(20/0.12SPC+PE1.8)*1P+COTTON YARN+AL-FOIL+BD16*7/0.12+BD16*8/0.12+PVC8.0





Very low high-frequency attenuation.

High-frequency phase change is extremely low.

Ultra Low Capacitance Star Quad



3070100190 0.251mm2 (Dual) 6.0mm FPE Black

- Improve the fatal flaw of star quad cable; core-core 35.5pF/1m, parallel for balance 79.5pF/1m.
- Aluminum Foil and Braid double shield.

(25/0.08+FPE1.5)*4C+COTTON YARN+AL-FOIL+BD16*6/0.10TC+PVC6.0



For the star quad structure, this is very

low high-frequency attenuation.



SVC675V-BK-PG-190-□M

Male XLR to Female XLR XLR Black Shells and Gold Plated Pins 3070100190 Star Quad Cable

※ XLR Type: SVP555V-BK-PG, SVP556V-BK-PG





We use industry stardards to check cables.

For the star quad structure, this is a ultra low high-frequency phase change.