

Speaker Cable

Pro Audio Market

XLPE Twisted Pair Speaker Cable



- Blue jacket.
- Use high-quality XLPE insulation and with twisted to reduce external interference.

Musical Instrument Market

No-Twisted Speaker Cable



- Black jacket.
- Use PVC insulation, parallel type structure, economic savings.

SKC888 Series Female to Male Speaker Cable

SKS888TX

SVP562TX + SVP563LTX
40A 4P, Max 10AWG

40A Loading Watt, Amp, Volt			
Resistance	Watt	Amp	Volt
2ohm	3200	40	80
4ohm	6400	40	160
8ohm	12800	40	320



SKS888WP-P

SVP562-GY-WP
+ SVP563L-M-P
25A 4P, Max 12AWG



Item No. Rule:

① - ② - ③ - ④ - ⑤

SKC888 WP-P - 2C - 20151 - 25M Example


	Remark	Define	Remark	Define
①	SKC870	Female to Female Speaker Cable	SKC888	Female to Male Speaker Cable
	SKC870 Connector Type		SKC888 Connector Type	
	(Default)	SVP562-C*2	-P	SVP562-C + SVP563L-M-P
	N	SVP562N-C*2	N-P	SVP562N-C + SVP563L-M-P
②	TX	SVP562TX*2	TX	SVP562TX + SVP563LTX
	WP	SVP562-GY-WP*2	WP-P	SVP562-GY-WP + SVP563L-M-P
	XQ	SVP562X-Q*2	XQ-P	SVP562X-Q + SVP563L-M-P
	L	SVP562L-GY-8P	L-P	SVP562L-GY-8P + SVP563L-M-P
	2C	Wiring Link Type	4P2C/Star Quad Parellel	
	4C		4P4C	
③	6C		8P6C	
	8C		8P8C	
④		Cable Item No. Final 5 Number		
⑤		Length: 2/5/10/15/20/25m		

※ In order to reduce cable fillers, if you want to use 2C large-diameter cables, you can choose 4C products to do star-quad parallel connection.
For Example:
make 6mm² 2C by 3.235mm² 4C, make 4mm² 2C by 2.0mm² 4C.


③ Wiring Link Type

4 Pins


2C: 4P2C



2C: Star Quad Parellel




4C: 4P4C




8 Pins

6C: 8P6C



8C: 8P8C



Cable Guide-
Speaker Cable