Aluminum Foil Shield Balance Microphone Cable for Installation
鋁箔型屏蔽固定安裝用平衡式麥克風線

- Tubular outer jacket, densely twisted, thick conductor, low capacitance, and few high-frequency attenuation.
- 管狀外被、對絞密、導體粗、電容低且高頻衰減極少。

※ New Update Item: 3070100204, Old Item: 3070101828

Item no. 型號	Jacket Color 外被顏色	Conductor 導體	Jacket OD 外徑
3070100204 BN8761	Gray	(11/0.20TC+PE1.6)*1P	4.5mm

Item No. 型號	3070100204 BN8761
Wire Information 線材資料	(11/0.20TC+PE1.6)*1P+DW11/0.20TC +AL-FOIL+PVC4.5
Main Conductor(AWG) 主要導體截面積	22AWG
Main Conductor(mm^2) 主要導體截面積	0.345mm^2

Electrical Performance 電氣性能

Cond.D.C.R. ohm/1km 導體電阻	54.05Ω			
Shield.D.C.R. ohm/1km 屏蔽電阻	50Ω			
Capacitance(pF/m) 電容值	C1	60.7	C0	122.3
Inductance(μH/m) 電感值	L1	0.7	L0	0.5
Impedance(ohm) 特性阻抗	107Ω			
Voltage Breakdown 絕緣承受電壓	300V			

Mechanical Performance 機械性能

Flex Life Number of Times load 500g+/-30° 搖晃壽命次數負載 500g 角度+/-30°	>50000
Tensile Strength (26°C, 65%RH) 拉伸斷裂力量	>33kgf
Applicable Temperature 建議工作溫度	-20°~+60°C(-4°~+140°F)
Peak Temperature 極限工作溫度	-20°~+70°C(-4°~+158°F)
100m Weight(kg) 100m 重量	2.8+/-0.2

※ Electrical performance may have manufacturing tolerances and measurement errors. At the time of editing, every effort has been made to ensure its authenticity.
電氣性能可能存在製造公差與量測誤差；本資料在編輯時已盡力保證其真實性。