

RJ45 Shell

IP66 Waterproof Cat6A Shark Series

SVP591X

Internal Thread on Shell
※ Without RJ45 Connector.

SVP591X-C6A-RJ23

SVP591X Shell +
23AWG Cat6A Plug
※ The shell is marked with Cat6A.
※ SVP591X-C6A-RJ24 is 24AWG.
※ SVP591X-C6A-RJ26 is 26AWG.



Fast-locked Type

① RJ45 Press Button

After locked the front Zinc shell, the button is disabled. Make it have a protective cover effect, and immediately compatible with normal RJ45 socket and etherCON®.

② The shortest shell structure minimizes torque.

The torque is the smallest when connected with socket.

※ SVP591L with two-stage design, but etherCON® Body has only one side grounding. The grounding ability is weak, the compatibility of some layer 1 protocols will be poor.

SVP591L

※ Without RJ45 Connector.



SVP591L-BK

Electrophoresis Black Shell
※ Without RJ45 Connector.



Screw Type

SVP591

※ Without RJ45 Connector.




SVP591-BK


Electrophoresis Black Shell
※ Without RJ45 Connector.



Assembly Demonstration



1. Separate into four parts:
two screws, upper-shell,
lower-shell.



2. Load RJ45 connector along
the track.



3. Press upper-shell down-ward.



4. Lock screws and it will be done.

Item No.	Two-stage design	Without Install Tool	Nickel Finish Shell	Scope of Application
SVP591X	•	•	•	etherCON® Socket
SVP591L	•	•	•	Normal RJ45 Socket/etherCON® Socket * AES50 & MAD1 not recommended to use.
SVP591			•	etherCON® Socket

※ etherCON® trademark belongs to Neutrik®.