

Optical Fiber Cable Reel

Global Local Easy-maintenance All Around The World
Adaptable to Third-party Media Converter
Easy to Use Fantail

- Multi-core Integrated, 4 to 6 cores per single reel.
- Meet the requirement of duplicated control network.
- 62.5μm multi-mode fiber accepts single-mode and multi-mode SFP.
- Dirty fantail and broken can be easily replaced, to ensure system security.
- Jump out the traditional patch cors design.
- Use solder with "MULTI CON" or flat box to keep the optical fiber storage.
- Provide patch cord to adapt different machines.
- Communication standard LC connector.
- Communication standard flange interfacing link.
- With cable reel 150 and 200m for option.



※ The copyright of the image belongs to AJA.



LC to LC Patch Cord EVA Proof Box



SFH-4M6A-LCB-150M



SFHP-6M6A-LCSG-150M



SFWC-6M3A-LCSG-500M

Fiber Core			4C		6C		6C	
Fiber Proof and Jacket			Armored with Braid					
Cable Reel (Please refer to page 47.)			Metal SDC-RH380-U4	Plastic SDCP-RH380-U5	Metal SDC-RH380-U4	Plastic SDCP-RH380-U5	Metal, Red Wheels SDC-R480	
Reel's Panel Connector			LC*6 (5 and 6 without link fiber.)		LC*6			
Terminal's Connector								
Terminal Type and Color			BMDC	Flat Box Multi-mode: Orange Single-mode: Yellow	BMDC	Flat Box Multi-mode: Orange Single-mode: Yellow	Flat Box Multi-mode: Orange Single-mode: Yellow	
Length			150/200m					300/500m
Patch Cord Package			10pcs 2m + EVA Box			14pcs 2m + EVA Box		14pcs 2m + EVA Box
			*We will provide extra 2pcs patch cords as backup.					
			*Patch cords can be upgraded to 12 and 16pcs.					
			Item No.					
Patch Cord Type	Multi-mode 62.5/125µm	LC-LC	SFH-4M6A-LCB-□M	SFHP-4M6A-LCSG-□M	SFH-6M6A-LCB-□M	SFHP-6M6A-LCSG-□M	SFWC-6M6A-LCSG-□M	
		LC-SC	SFH-4M6A-SCB-□M	SFHP-4M6A-SCSG-□M	SFH-6M6A-SCB-□M	SFHP-6M6A-SCSG-□M	SFWC-6M6A-SCSG-□M	
	Multi-mode OM3 Class 50/125µm	LC-LC	SFH-4M3A-LCB-□M	SFHP-4M3A-LCSG-□M	SFH-6M3A-LCB-□M	SFHP-6M3A-LCSG-□M	SFWC-6M3A-LCSG-□M	
		LC-SC	SFH-4M3A-SCB-□M	SFHP-4M3A-SCSG-□M	SFH-6M3A-SCB-□M	SFHP-6M3A-SCSG-□M	SFWC-6M3A-SCSG-□M	
	Single-mode 9/125µm	LC-LC	SFH-4SA-LCB-□M	SFHP-4SA-LCSY-□M	SFH-6SA-LCB-□M	SFHP-6SA-LCSY-□M	SFWC-6SA-LCSY-□M	
		LC-SC	SFH-4SA-SCB-□M	SFHP-4SA-SCSY-□M	SFH-6SA-SCB-□M	SFHP-6SA-SCSY-□M	SFWC-6SA-SCSY-□M	
Option			Flight Case					

※ Use Limitation:

Multi-mode: Between fiber with SFP, without other patch cord, the longest 240m (conservatively recommended value).

Single mode: Between fiber with SFP, has twice third-party connection (TXRX each time) 350m~10km (conservatively recommended value).