


台灣日昇電子股份有限公司  
**ISSUE APPROVED**  
 發行核可 本文件與簽核紙本正本相符

- Notes(備註):
- SR® trademark is carved by laser.  
(SR®商標為雷射雕刻)  
Push button with a flower logo.  
(按鍵上有小花商標)
  - Pin No.1 solder side compare with other pin solder side has less than 1±0.15  
(1號插針的焊杯端面比其他插針的焊杯端面低1±0.15)
  - Insulator with a S.R logo  
(塑粒上有SR商標 SR)
  - ★4. Remove O-ring used for cable O.D.: 3.3~4.8mm,  
Standard connector used for cable O.D.: 5~6.8mm(below)  
(拿掉O型圈適用線徑3.3~4.8mm, 標準接頭適用線徑5~6.8mm以下)

10	螺套+尾套(CAP+BOOT)	PA6+TPR	黑+灰(BK+GY)	1	4301060117
9	夾線爪(CABLE CLAMP)	POM	白色(WHITE)	1	4301070022
8	O型圈(O-RING)	SILICON	黑色(BLACK)	1	1209100039
7	插孔(FEMALE PIN)	PHOSPHOR BRONZE	鍍銀(SILVER)	3	4401120117 (SVP556S-0-SR)
6	塑粒(INSULATOR)	PA	黑色(BLACK)	1	
5	鋼片(LATCH)	STAINLESS STEEL	鍍錫(TIN)	1	
4	按鍵固定片(FIXED SHEET)	STAINLESS STEEL	鍍鎳(NICKEL)	1	3103040167
3	O型圈(O-RING)	SILICON	黑色(BLACK)	1	1209100051
2	按鍵(PUSH BUTTON)	ZZnAL4-1	鍍鎳(NICKEL)	1	3103040174
1	鋅殼(DIE CAST SHELL)	ZZnAL4-1	電泳黑(Electro-coating black)	1	3103040111
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.

DIMENSIONS ARE IN MILLIMETERS		APPROVED	DATE
UNLESS OTHERWISE SPECIFIED TOLERANCES		吳碧珊	2020-03-18
ANGLES = ±5°		CHECKED	DATE
UP TO 6 = ±0.2		吳碧珊	2020-03-18
6-40 = ±0.4		DRAWN	DATE
40-120 = ±0.6		吳碧珊	2020-03-18
120-315 = ±1		FILE NO.	D:\CAD\SVP556\5112010571_
ABOVE 315 = ±1.6			SVP556V-BK_CA001A2
THIRD_ANGLE	☉	ERP LINK:	5112010571
SCALE	1/1	PART NO.	SVP556V-BK

 <b>日昇電子股份有限公司</b> SUN RISE EXACT INDUSTRIAL CO.		TITLE	
		3 PIN XLR FEMALE CONNECTOR	
PART NO.	SVP556V-BK	REV.	A2

F  
E  
D  
C  
B  
A

F  
E  
D  
C  
B  
A

1 2 3 4 5 6 7 8

1 2 3 4 5 6 7 8